

HDMI 1.4b 1:2 Splitter Features

- HDMI 1-to-2 active Splitter with Equalization & Pre-emphasis up to 340 MHz Clock
- Support up to 3.4Gbps TMDS Serial Link Compliant with HDMI 1.4b requirement
- HDMI data rate of 3.4Gbps provides a 1920x1080 @ 60Hz resolution or 4K @30Hz

USB-COM232 Features

- Adds two RS-232 serial ports by connecting to USB easy plug & play installation
- Provide USB2.0 Hi-Speed(480Mbps) interface and works with USB 1.1 & 2.0 Host and Hub ports
- Industry Standard FTDI chip set & device drivers for maximum compatibility
- Microsoft Windows® WHQL-certified, Mac OS X, Linux and Windows CE device drivers
- Installs as two standard Windows COM ports, COM port number can be changed to any available COM port number, including COM1 to COM4
- Supports Windows Server 2008, 2003, 10, 8, 7, Vista, XP 2000, Linux, Mac OS X
- FIFO: 4K byte transmit buffer, 4K byte receive buffer
- Serial port speed up to 1Mbps
- LEDs indicate USB Enumeration, Rx/D, Tx/D for monitoring port status & easy diagnostics

Common Features

- External Power Supply 4.5 to 36 VDC
- Powered by USB port. No external power adapter required
- Industrial operating temperature range -40°C to +85°C
- Dimension 80X70mm

